



THREAD AND COMPRESSION BONDING

**A QUICK, VERY STRONG AND EASY SOLUTION
TO INSTALLING AND REPAIRING FITTINGS.**

Super Power Thread and Compression Bonding is a strong, super fast-dry set thread bond designed for high vibration environments such as plumbing, refrigeration and industrial applications.

Recommended for use on threaded galvanised steel, iron, brass, copper, aluminium and stainless steel. Great for use as a positive lock and seal on threaded fasteners.

Super Power Thread and Compression Bonding prevents leaks from threaded plumbing joints and is suitable for use by Gas Safe registered installers.

Applications:

Drinking Water, Hot Water, Heating, Natural Gas, Oil and LPG





Benefits:

- Extremely strong bond
- Tested at 15 BAR within 60 seconds
- Sets in 60 seconds
- No need to have different sealers
- Never need to undo to add PTFE (Thread sealant tape)
- For use with all metal threads
- Easy application
- High Mechanical Resistance
- Solvent and water-resistant once cured
- Prevents loosening of vibrating parts
- Conforms to The Water Supply (Water Fittings) Regulations 1999

Product Code:

50ml Thread and Compression Bonding - PGPSPTB

Instructions For Use:

WEAR PPE / SHAKE WELL BEFORE USE

1. Clean pipe and fitting with an abrasive P60 cloth to form grooves.
2. Shake bottle and apply liquid to the inside of the fitting and outside of pipe.
3. Insert copper pipe into fitting and rotate 360° to provide adhesive distribution.
4. Flush any remaining adhesive from the pipe and fitting.
Dries in 60 seconds, wait 5 mins cure for structural bond.

Safety

Contains hydroquinone monomethyl ether. May produce an allergic reaction. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Avoid breathing dust/fumes/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of water/soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *In Germany not to be used in gas installation according to DVGW TRGI 2008. Not to be used on Oxygen lines.

Safety data sheet can be obtained if required. For product support call: 0800 368 9145.

Manufactured by:

Prime Global Products Ltd. PGP & The Potato Store, Station Road,
Firsby, Spilsby, England, PE23 5PX www.superpower.store

